

QUOTATION SHEET 2024

亮洋電子科技有限公司 LIANGYANG ELECTRONIC TECHNOLOGY CO.,LTD



liangYang

RoHS CB

CE EMI UL GS



T: +86-760-8575-5707

M: +86-135-3551-6097

Skype: liangyangtech

Wechat: ledlumi

Web:

www.liangyangtech.com

Factory:

BolinTai Industrial Park ,No. 1Rd.,

1st Industrial Zone,


Baihua, Guangming St., Guangming,

Shenzhen, Guangdong, China

Big project director :
INFO@LIANGYANGTECH.COM

★★★ Free sample testing is available. ★★★

UFO LED High Bay Light 97 SERIES

Date	: 2024.03				Package	: Neutral box or customized design for large quantity.								
MOQ	: 50 PCS each				Payment terms	: T/T in advance. 30% deposit, balance before shipment. 100% for the sample								
Valid date	: 30 Days				Delivery date	: 3-7 days for samples; 10-20 days for bulk order.								
Shipping per	: By Express / Air / Sea				After service	: 2 /3 years warranty								
Port of loading	: Zhongshan / Guangzhou / Shenzhen				Trade terms	: Ex-works								
Certificate	: CE & RoHS, RCM													
Item No.	Picture	Specification			Dimension (mm)	Beam Angle	PCS /CT N	MEAS (cm)			Weight KG	Price USD/PC	Remark	
		Watt	Details	Color				L	W	H				
LY-GK10097		100	LED HIGH BAY LIGHT Input: AC220-240V 50/60Hz Power Factor: >0.9 LED Chip: Epistar 3030 1W 148PCS Luminous Flux: ≥10000 Ra>70 Material: Aluminum IP65 Driver: DOB Material: Aluminum + Acrylic Surge protection : 2500V Inner Box Size: 26.2*26.2*5.5cm	3000K - 6500K	Φ260*H85	90°	10	54	29.5	28	1.25			
LY-GK15097		150	LED HIGH BAY LIGHT Input: AC220-240V 50/60Hz Power Factor: >0.9 LED Chip: Epistar 3030 1W 222PCS Luminous Flux: ≥15000 Ra>70 Material: Aluminum IP65 Driver: DOB Material: Aluminum + Acrylic Surge protection : 2500V Inner Box Size: 31.2*31.2*6cm	3000K - 6500K	Φ310*H95	90°	10	64	32	33	1.7			
LY-GK20097		200	LED HIGH BAY LIGHT Input: AC220-240V 50/60Hz Power Factor: >0.95 LED Chip: Epistar 3030 1W 296PCS Luminous Flux: ≥20000 Ra>70 Material: Aluminum IP65 Driver: DOB Material: Aluminum + Acrylic Surge protection : 2500V Inner Box Size: 35.2*35.2*6.5cm	3000K - 6500K	Φ350*H100	90°	10	72	34.5	36.5	2.6			
LY-GK10097		100	LED HIGH BAY LIGHT Input: AC85-265V 50/60Hz Power Factor: >0.95 LED Chip: Epistar 3030 1W 120PCS Luminous Flux: ≥10000 Ra>70 Material: Aluminum IP65 Driver: Constant current Non-isolation Material: Aluminum + Acrylic Surge protection : 4000V	3000K - 6500K	Φ275*H115	90°	10	44.5	29	54.5	1.6		2years	
LY-GK15097		150	LED HIGH BAY LIGHT Input: AC85-265V 50/60Hz Power Factor: >0.95 LED Chip: Epistar 3030 1W 192PCS Luminous Flux: ≥15000 Ra>70 Material: Aluminum IP65 Driver: Constant current Non-isolation Material: Aluminum + Acrylic Surge protection : 4000V	3000K - 6500K	Φ310*H120	90°	5	44.5	33.5	33	2		2years	
LY-GK20097		200	LED HIGH BAY LIGHT Input: AC85-265V 50/60Hz Power Factor: >0.95 LED Chip: Epistar 3030 1W 240PCS Luminous Flux: ≥20000 Ra>70 Material: Aluminum IP65 Driver: Constant current Non-isolation Material: Aluminum + Acrylic Surge protection : 4000V	3000K - 6500K	Φ345*H125	90°	5	46	37.5	37	2.9		2years	

